



## CC-9006W/WH



- ✓ INDOOR TRI-AXIS SONY SUPER HAD DOME CAMERA
- ✓ FLEXIBLE CEILING OR WALL MOUNTING
- ✓ HIGH SENSITIVITY & 550 TV LINES RESOLUTION




### Specifications

### CC-9006W/WH

Model	CC-9006W	CC-9006WH
Pick up Element	Sony 1/3" Color Super HAD CCD Sensor	Sony 1/3" Color H.Q. 1 Super HAD CCD Sensor
Effective Picture Element	NTSC: 510(H)x492(V) PAL: 500(H)x582(V)	NTSC: 81(H)x508(V) PAL: 795(H)x596(V)
Horizontal Resolution	420 TVL	550 TVL
Minimum Illumination	0.2 LUX @ F2.0	0.4 LUX @ F2.0
S/N Ratio	More than 48dB	
Auto Electronic Shutter	NTSC:1/60s~1/100,000s, PAL:1/50s~1/110,000s.	
Auto Iris Control	Not Available	
Flickerless Mode	NTSC:1/60s, PAL:1/120s	
Auto Gain Control	High/Low	
Auto White Balance	Yes. (2500K~9500K)	
Back Light Compensation	On/Off	
Gamma Characteristic	0.45	
Lens Furnished	Board Lens 3.6mm/F2.0 (option: 2.5, 6, 8, 12mm)	
Synchronous System	Internal, Negative sync.	
Video Output	1 Vp-p/75 Ohms	
Power Supply	DC12V 142mA	DC12V 220mA
Operating Temperature	-10°C to 50°C (14°F to 122°F)	

\* Specifications Subjected to Change Without Prior Notice



## CC-9006WL1/WHL1



- ✓ INDOOR TRI-AXIS SONY SUPER HAD DOME CAMERA
- ✓ AUTO IRIS & VARI-FOCAL 3.7~12MM LENS
- ✓ FLEXIBLE CEILING OR WALL MOUNTING
- ✓ HIGH SENSITIVITY & 550 TV LINES RESOLUTION



### Specifications

### CC-9006WL1/WHL1

Model	CC-9006WL1	CC-9006WHL1
Pick up Element	Sony 1/3" Color Super HAD CCD Sensor	Sony 1/3" Color H.Q. 1 Super HAD CCD Sensor
Effective Picture Element	NTSC: 510(H)x492(V) PAL: 500(H)x582(V)	NTSC: 811(H)x508(V) PAL: 795(H)x596(V)
Horizontal Resolution	420 TVL	550 TVL
Minimum Illumination	0.2 LUX @ F2.0	0.4 LUX @ F2.0
S/N Ratio	More than 48dB	
Auto Electronic Shutter	NTSC:1/60s~1/100,000s, PAL:1/50s~1/110,000s.	
Auto Iris Control	Built-in DC Drive Iris Control	
Flickerless Mode	NTSC:1/60s, PAL:1/120s	
Auto Gain Control	High/Low	
Auto White Balance	Yes. (2500K~9500K)	
Back Light Compensation	On/Off	
Gamma Characteristic	0.45	
Lens Furnished	Vari-Focal 3.7~12mm / F1.6 (option: 9-22mm)	
Synchronous System	Internal, Negative sync.	
Video Output	1 Vp-p/75 Ohms	
Power Supply	DC12V 142mA	DC12V 220mA
Operating Temperature	-10°C to 50°C (14°F to 122°F)	

\* Specifications Subjected to Change Without Prior Notice

