




PRO-9650S



- ✓ PROFESSIONAL COLOR HIGH RESOLUTION DAY & NIGHT CAMERA
- ✓ HIGH SENSITIVITY & LOW ILLUMINATION ~ 0.2 LUX @ F1.2
- ✓ BUILT-IN COLOR BY DAY & B/W BY NIGHT FUNCTION
- ✓ AUTO IRIS VIDEO DRIVE & DC DRIVE LENS SUPPORTED
- ✓ AUTO GAIN CONTROL (AGC), AUTO ELECTRONIC SHUTTER (AES), BACK LIGHT COMPENSATION (BLC-ON/OFF) FUNCTIONS
- ✓ 24V AC & 12V DC DUAL VOLTAGE



* Lens not included



* Best Night Vision Effect with IR Cut Filter Lenses

Specifications

Pro-9650S

Image Pick-Up Device	1/3" SONY HR Super HAD CCD Sensor
Effective Picture Element	NTSC: 768(H)x494(V) / PAL: 752(H)x582(V)
Horizontal Resolution	550 TV Lines
Minimum Illumination	0.2 Lux @ F1.2
Color turns into B/W(Approx.)	Automatically trigger on when illumination < 3Lux (F1.2)
S/N Ratio	More than 48dB
Auto Electronic Shutter	NTSC:1/60s~1/100,000s,PAL:1/50s~1/110,000s
Auto Iris Control	Video Drive Lens & DC Drive Lens Supported
Flickerless Mode	NTSC: 1/100s, PAL: 1/120s On/Off
Gamma Characteristic	0.45
Lens Mount	C or CS mount adjustable
Auto Gain Control	High/Low
Auto White Balance	Yes (2500K~9500K)
Back Light Compensation	On/Off
Synchronous System	Internal, Negative Sync.
Video Output	1 Vp-p/75 Ohms, BNC Connector
Power Supply	12V DC or 24V AC (Dual Voltage)
Power Consumption	< 3.2W
Operating Temperature	-10°C to 50°C / 14°F to 122°F

* Specifications Subjected to Change Without Prior Notice

PRO-35X



- ✓ PROFESSIONAL AUTO FOCUS ZOOM CAMERA
- ✓ 35X OPTICAL ZOOM
- ✓ BUILT-IN ICR: DAY & NIGHT FUNCTION
- ✓ ON SCREEN DISPLAY (OSD) SET-UP MENU
- ✓ CAMERA CONTROL VIA RS-485
FUNCTIONS: AI, AWB, AGC, BLC, FL, AUTO FOCUS, AUDIO
- ✓ SUPPORTED PROTOCOLS: PELCO P & PELCO D



Specifications

Pro-35X

Image Pick-Up Device	1/4" SONY Super HAD CCD Sensor
Effective Picture Element	NTSC: 811(H)x508(V) / PAL: 795(H)x595(V)
Horizontal Resolution	550 TV Lines
Minimum Illumination	0.5 Lux @ F1.65
Day & Night Function	AGC/DAY/NIGHT/CDS (ICR)
S/N Ratio	More than 48dB
Auto Electronic Shutter	NTSC:1/60s~1/100,000s,PAL:1/50s~1/110,000s
Auto Iris Control	Video Drive Lens & DC Drive Lens Supported
Flickerless Mode	NTSC: 1/100s, PAL: 1/120s On/Off
Gamma Characteristic	0.45
Lens	35X Optical Zoom (F=3.6mm ~126mm, F1.65~4.2)
Electronic Shutter	Auto / Manual / Shutter / Iris
White Balance	Auto / Manual
RS485 Zoom Control	RS485; Baud Rate: 2400, 4800, 9600
RS485 Protocol	Pelco P & Pelco D
Video Output	1 Vp-p/75 Ohms, BNC Connector
Power Supply	12V DC
Power Consumption	340mA
Operating Temperature	-10°C to 50°C / 14°F to 122°F

* Specifications Subjected to Change Without Prior Notice

