

## JD-P201



- Color 1/3" Sharp HAD CCD
- Resolution: 420 TV Lines
- Min. Illumination: 0.4 Lux
- Furnished with 3.6mm Lens
- 12V DC Low Power Consumption



### Specifications

Model	JD-P201
Pick Up Element	1/3" Sharp Color HAD CCD
Number of Pixels	NTSC:512(H)x492(V) / PAL:512(H)x582(V)
Resolution	420 TV Lines
Minimum Illumination	0.4 Lux/F2.0
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	NTSC:1/60s~1/100000s, PAL:1/50s~1/100000s
Lens	3.6mm/F2.0
IRIS Mode	AES
Gain Control	Auto
White Balance	ATW
Video Output	1.0Vp-p composite, 75Ω
Power Source (±10%)	12V DC
Current Consumption (±10%)	110mA
Dimension (mm)	100(Ø)x60(H)

\* Specifications Subjected to Change Without Prior Notice

## JD-203



- Color 1/3" Sony Super HAD CCD
- Resolution: 420 TV Lines
- Min. Illumination: 0.1 Lux
- Furnished with 3.6 or 6mm Lens
- Optional 6mm Lens
- 3 Axis Flexible Mounting
- 12V DC Low Power Consumption



### Specifications

Model	JD-203
Image Sensor	1/3" Sony Color Super HAD CCD
Picture Elements	NTSC:510(H)x492(V) / PAL:500(H)x582(V)
Resolution	420 TV Lines
Minimum Illumination	0.1LUX / F2.0
S/N Ratio	More than 48dB
Electronic Shutter	NTSC: 1/60~1/100000 sec, PAL: 1/50~1/100000 sec
Gain Control	Auto
White Balance	2500°K~9500°K
Scanning System	Interlace 2:1
Gamma	0.45
Lens	Board Lens 3.6mm / F2.0 (Optional 6.0mm)
Sync System	Internal
Video Output	1.0Vp-p/75 Ohms
Power Supply	12V DC ± 10%
Power Consumption	140mA (Max)

\* Specifications Subjected to Change Without Prior Notice

## JD-205IR / W



- Color 1/3" Sony Super HAD CCD
- Resolution: 420 TV Lines
- Furnished with 3.6 mm Lens
- Optional 6mm Lens
- 24 IR LEDs; Night Vision: 50 ft.
- 3 Axis Flexible Mounting
- 12V DC Low Power Consumption



### Specifications

Model	JD-205IR / JD-205IR-W
Pick Up Element	1/3" Sony Super HAD CCD
Number of Pixels	NTSC:510(H)x492(V)
Resolution	420 TV Lines
Minimum Illumination	0 Lux (IR On)
IR LED	24 pcs
IR Effective Range	Up to 50 ft.
S/N Ratio	More than 52dB
Lens	3.6mm (Optional 6mm)
Video Output	1.0Vp-p, 75Ω Y/C separated
Power Source (±10%)	12V DC
Housing	IP65
Operating Temperature	-20°C~50°C (-4°F~122°F)

\* Specifications Subjected to Change Without Prior Notice