







CC-4404C



CC-4405C



FEATURES

Ultra-Mini: It is about the size of a QUARTER. Easily to be disguised, converted into a hidden/covert camera.

CC-4404C

- SHARP 1/3" Solid-state image CCD sensor
- 380 TV Lines of Horizontal Resolution
- Minimum illumination of 0.4 Lux
- AES, AWB

CC-4405C

- SHARP 1/3" Solid-state image CCD sensor
- 380 TV Lines of Horizontal Resolution
- Minimum illumination of 0.4 Lux
- AES, AWB

SPECIFICATION

Model Number	CC-4404C	CC-4405C
Image Pick-up Device	SHARP 1/3" Solid-state image CCD sensor	
Effective Picture Element	NTSC: 512(H)x492(V), PAL: 512(H)x582(V)	
Horizontal Resolution	380 TV lines	
Minimum Illumination	0.4 LUX @ F2.0	
S/N Ratio	More than 48dB	
Auto Electronic Shutter	NTSC: 1/60s~1/100,000s, PAL: 1/50s~1/110,000s	
Gamma Characteristic	0.45	
Lens Furnished	3.6 mm/F2.0 Board Lens	3.8 mm/F2.0 Corn Lens
Auto White Balance	Color Temperature: 2500K~9500K	
Synchronous System	Internal, Negative Sync.	
Video Output	1 Vp-p / 75 Ohms	
Power Consumption	1.5W	
Power Supply	12V DC	
Operating Temperature	-10 °C ~ 50 °C (14 °F ~ 122 °F)	

*Specifications subject to change without notice