

CM-1001A



CM-1002A



CM-1020A



CM-1004AH



CM-1021AH



SPECIFICATION

Model Number	CM-1001A	CM-1002A	CM-1020A	CM-1004AH	CM-1021AH
CRT	12" 90° B/W P4 glare	15" 90° B/W P4 glare	20" 90° B/W P4 glare	14" 90° Color P22	21" 90° Color P22
Scanning Frequency	EIA: 15.750KHz/60Hz, CCIR: 15.625KHz/50Hz			NTSC: 15.750KHz/60Hz, PAL: 15.625KHz/50Hz	
Resolution	800 TV line	1000 TV line		400 TV line	500 TV line
Bandwidth	10MHz (-3dB)	—————	12MHz (-3dB)	—————	
Video Input	Composite Video 1 Vp-p				
Input Power	100V~240V AC 50/60 (Auto)				
Power Consumption	30 W (Max.)	35 W (Max.)	36 W (Max.)	60 W (Max.)	90 W (Max.)
Video Connectors	BNC In/Out x 1 set			BNC In/Out x 1 set	BNC In/Out x 2 set
Audio Connectors	RCA In/Out x 1 set				S-VHS Y/C In/Out x 1 set
Dimension (mm)	304x320x310(WxHxD)	350x353x360(WxHxD)	472x450x360(WxHxD)	350x353x360(WxHxD)	492x464x482(WxHxD)

*Specifications subject to change without notice